

Part# IP 1324-1806

Product Name: IP-PDU

Category: Monitored

Product Summary: 32A, 100-240VAC, 18×IEC C13 + 6×IEC C19 outlets, 3m power cord with IEC 60309 2P + E (IP44)

Physical Configuration: 0U, Chassis dimensions (H×W×D) =L×50×44.4 mm

Characteristics

- **PDU level**
 - Amps(A), volt(V) metering
 - Power(kVA), energy(kWh) metering
- **Environment monitoring compatibility**
 - Standard sensor: 1×T/H sensor
- **Hot-swap**
 - Network metering module
- **Software features**
 - Threshold setting of current/voltage/temperature/humidity
- **Design features**
 - Daisy-chain capable
 - Locking IEC outlets
 - Color coded outlets
- **Access Method**
 - Support 10/100M bit Ethernet port
 - Support network communication protocol including TCP, UDP, HTTP, SMTP
 - Support 1 level account password security, IP/MAC filter
 - Support various web browsers like IE, Firefox, Chrome, Safari

Specifications

Input	
Input voltage	100-240VAC
Input current	32A
Input Frequency	50/60Hz
Power cord length	3m
Input Plug	IEC 60309 32A 2P + E IP44
Output	
Output configurations	18×IEC C13 + 6×IEC C19
Output voltage	100-240VAC
Output current	C13 (10A), C19 (16A)
Overload protection	2×1P (16A) Air circuit breakers
Physical	
Dimension (H x W x D)	L×50×44.4 mm
Shipping dimension (H x W x D)	L×150×85 mm
Product color	Black
Environment	
Temperature (Operating / Storage)	0 ~ 45°C / -20 ~ 70°C
Humidity (Operating/ Storage)	5 ~ 95% RH / 5 ~ 95% RH Non-condensing
Maximum elevation, above MAL (Operating/ Storage)	0 ~ 3,000m / 0 ~ 15,000m
Compliance	
EMC verification	EN55022, EN61000, FCC Part 15 Class A, ICES
Safety verification	LVD
UL	NO
Environmental verification	ROHS