

# Part# IP 3324-2004

**Product Name:** IP-PDU

**Category:** Monitored

**Product Summary:** 3×32A, 200-415VAC, 20×IEC C13 + 4×IEC C19 outlets, 3m power cord with IEC 60309 3P + N + E (IP44)

**Physical Configuration:** 0U, Chassis dimensions (H×W×D) = L×50×44.4 mm

## Characteristics

- **PDU level**
  - Amps(A), volt(V) metering
  - Power(kVA), energy(kWh) metering
  
- **Environment monitoring compatibility**
  - Standard sensor: 1×T/H sensor
  
- **Hot-swap**
  - Network metering module
  
- **Software features**
  - Threshold setting of current/voltage/temperature/humidity
  
- **Design features**
  - Daisy-chain capable
  - Locking IEC outlets
  - Color coded outlets
  
- **Access Method**
  - Support 10/100M bit Ethernet port
  - Support network communication protocol including TCP, UDP, HTTP, SMTP
  - Support 1 level account password security, IP/MAC filter
  - Support various web browsers like IE, Firefox, Chrome, Safari

# Specifications

| Input                                             |                                             |
|---------------------------------------------------|---------------------------------------------|
| Input voltage                                     | 200-415VAC                                  |
| Input current                                     | 3×32A                                       |
| Input Frequency                                   | 50/60Hz                                     |
| Power cord length                                 | 3m                                          |
| Input Plug                                        | IEC 60309 32A 3P + N + E IP44               |
| Output                                            |                                             |
| Output configurations                             | 20×IEC C13 + 4×IEC C19                      |
| Output voltage                                    | 100-240VAC                                  |
| Output current                                    | C13 (10A), C19 (16A)                        |
| Overload protection                               | 3×1P (32A) Air circuit breakers             |
| Physical                                          |                                             |
| Dimension (H x W x D)                             | L×50×44.4 mm                                |
| Shipping dimension (H x W x D)                    | L×150×85 mm                                 |
| Product color                                     | Black                                       |
| Environment                                       |                                             |
| Temperature (Operating / Storage)                 | 0 ~ 45°C / -20 ~ 70°C                       |
| Humidity (Operating/ Storage)                     | 5 ~ 95% RH / 5 ~ 95% RH Non-condensing      |
| Maximum elevation, above MAL (Operating/ Storage) | 0 ~ 3,000m / 0 ~ 15,000m                    |
| Compliance                                        |                                             |
| EMC verification                                  | EN55022, EN61000, FCC Part 15 Class A, ICES |
| Safety verification                               | LVD                                         |
| UL                                                | NO                                          |
| Environmental verification                        | ROHS                                        |